



Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

## GALACTIC IV MULTI WATT & CCT SELECT UFO FIXTURE



The **Galactic IV Multi Watt & CCT Select UFO Fixture** is a DLC Premium high bay fixture with field-selectable output and CCT. This product can replace 9 high bay SKUs to reduce inventory stocking for distributors and contractors. It is ideal for warehouses and factories with an IP66 rating, high performance, and no maintenance for 50,000+ hours. Easy 1-10V control for dimming and DLC Premium qualifies for the maximum rebates, in many regions.

### FEATURES

- Field-selectable output and CCT
- UL and DLC Premium Listed
- 145 lm/W
- IP66
- 100-277VAC
- 6KV Surge protection
- 1-10V dimming

### APPLICATIONS

- Warehouse
- Convention Centers
- Sporting Arenas
- Big-box retail stores
- Cold storage facilities



# GALACTIC IV MULTI WATT & CCT SELECT UFO FIXTURE

## ORDERING INFORMATION

MODEL NO.	POWER	LUMEN (LM)	VOLTAGE	CRI	CCT	MIN. ORDER QUANTITY	US STOCK
ECO-1LED-ELHB-MW (80/100/150W)30/40/50K	80W	11600	100-277VAC	70+	3000K / 4000K / 5000K	2	Y
	100W	14500					
	150W	21750					
ECO-1LED-ELHB-MW (180/200/250W)30/40/50K	180W	27000	100-277VAC	70+	3000K / 4000K / 5000K	2	Y
	200W	30000					
	250W	37500					

## TECHNICAL SPECIFICATIONS

Optical Distributions	120°
CRI	70+
Efficacy	145 Lm/W
IP Rating	IP66
Input Voltage	100-277 VAC
Current	1.5A (@120V)
Power Frequency	50-60 Hz
Power Factor	>0.95
THD	<15%
Certifications	UL, DLC Premium, FCC
Housing Material	Corrosive resistant polyester powder coat finish. Aluminum alloy.
Rated Life (L70)	>50,000 Hours
Warranty	10 Years, 50,000 Hours Non-Prorated
Operating Temperature	-22° - 122°F
Controls	1-10V dimming

\*Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

\*IES files provided on request.

# GALACTIC IV MULTI WATT & CCT SELECT UFO FIXTURE

## CONTROLS

Control Options: 1-10V dimming. Output and CCT selectable. Motion sensor with remote control.

## OPTIONAL ACCESSORIES



Motion Sensor  
LOC-ANT-5-4T

(Compatible with remote control)



Remote Control  
LOD-RC-100



Emergency Driver  
LOC-HBEMDR-25WHV



PC Reflector

(For Multi Wattage Models Only)



60° lens

(For 300W model)

## MOUNTING OPTION:



U-Bracket

(For multi watt models)




8-foot cord

# GALACTIC IV MULTI WATT & CCT SELECT UFO FIXTURE


## PHOTOMETRICS

80W/100W/150W:



Maximum Candela = 10602.73 Located At Horizontal Angle = 0, Vertical Angle = 0  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
# 2 - Vertical Plane Through Horizontal Angles (90 - 270)


180W/200W/250W:



Maximum Candela = 30289.051 Located At Horizontal Angle = 0, Vertical Angle = 0  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
# 2 - Vertical Plane Through Horizontal Angles (90 - 270)

## DIMENSIONS

80W/100W/150W:



180W/200W/250W:

