


Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

## ARBITRUM LOW BAY FIXTURE



The **Arbitrum Low Bay Fixture** is ideal for hazardous locations, including petroleum, chemical, pulp & paper, foundries, manufacturing and more. This hazloc fixture is available in 30-70W, and with efficiency up to 140 lm/W. Class and Division ratings include CID1, CID2, CIID1, and CIID2. The Arbitrum is extremely durable with IP66 rating, IK10 rating, optional wireguard, and a 10-year non-prorated warranty.

### FEATURES

- Marking UL844 Hazardous Locations: CID1, CID2, CIID1, and CIID2
- 5 wattages: 30W, 40W, 50W, 60W, and 70W
- Up to 9,800 lumens and up to 140 lm/W
- IP66 rating
- IK10 impact rating
- Ceiling, stanchion, wall bracket, pendant and trunnion mount options
- Marine rated aluminum alloy housing, powder-coat finish, & stainless steel hardware
- Optional wire guard
- 10 year non-prorated warranty

### APPLICATIONS

- Oil and gas industry
- Mining
- Chemical
- Ocean, marine, and aerospace
- Metal treatment
- Food and alcohol industry
- Other high humidity, high dust, high temperature, and hazardous locations




## ORDERING INFORMATION

MODEL NUMBER	POWER	LUMENS	VOLTAGE	CRI	CCT	MIN. ORDER QTY	US STOCK
ECO-CGA-HA03-30W-ARB	30W	4,200	100-277VAC or 277-480VAC	70+/80+/90+	2000K-6500K 5000K standard Red, Green, Blue, Amber	2	Yes
ECO-CGA-HA03-40W-ARB	40W	5,600	100-277VAC	70+/80+/90+	2000K-6500K 5000K standard Red, Green, Blue, Amber	2	Yes
ECO-CGA-HA03-50W-ARB	50W	7,000	100-277VAC	70+/80+/90+	2000K-6500K 5000K standard Red, Green, Blue, Amber	2	Yes
ECO-CGA-HA03-60W-ARB	60W	8,400	100-277VAC or 277-480VAC	70+/80+/90+	2000K-6500K 5000K standard Red, Green, Blue, Amber	2	Yes
ECO-CGA-HA03-70W-ARB	70W	9,800	100-277VAC	70+/80+/90+	2000K-6500K 5000K standard Red, Green, Blue, Amber	2	Yes

## TECHNICAL SPECIFICATIONS


Optical Distributions	120°	Rated Life	77,000 hours – L90 175,200 hours – L80 282,900 hours – L70
CRI	70+ / 80+ / 90+	Warranty	10 Years or 50,000 hours non-prorated
CCT	2000K-6500K, 5000K standard, Red, Green, Blue, Amber	Net Weight	Ceiling mount: 8.3 kg (18.3 lbs) 25° Stanchion mount: 7.9 kg (17.4 lbs) Wall bracket: 9 kg (19.8 lbs) Pendant mount: 7.3 kg (16.1 lbs) Trunnion mount: 9 kg (19.8 lbs)
Efficacy	Up to 140 Lm/W (5000K, 70+CRI)	Finish	Gray marine rated powder-coated finish.
Input Voltage	100-277VAC or 277-480VAC (for 30W & 60W models only)	Mounting	Ceiling mount, 25° Stanchion mount, Wall bracket, Pendant mount, Trunnion mount
Power Frequency	50-60 Hz	Cable Entries	– Ceiling mount / Trunnion mount: 3/4" NPT, M25X1.5, M20X1.5 – Wall bracket / Pendant mount: 3/4" NPT, 1" NPT, M25*1.5, M20X1.5 – 25° Stanchion mount: 1-1/4" NPT, 1-1/2" NPT
Power Factor	>0.90	Operating Temperature	-40°F to +149°F
Surge Protection	30W/40W/50W: 4kV line-line, 6kV line-earth 60W/70W: 6kV line-line, 10kV line-earth	<p>*Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.</p> <p>*IES files provided on request.</p>	
Certifications	UL844 Hazardous Locations: – Class I, Division 1, Groups B, C, D – Class I, Division 2, Groups B, C, D – Class II, Division 1, Groups E, F, G – Class II, Division 2, Groups F, G – Class III – Class I, Zone 1, Group IIB plus hydrogen – Class I, Zone 2, Group IIB plus hydrogen – Zone 20 and Zone 21 – Zone 22 Wet Location & Marine Location rated.		
IP Rating	IP66		
Impact Rating	IK10		
EPA	0.05 m <sup>2</sup> (0.5 ft <sup>2</sup> )		
Housing Material	Aluminum alloy (<0.4% copper content), powder coat finish, clear glass, and stainless steel hardware.		

DIMENSIONS




Dimensions In/mm																		
Unit	Ceiling Mount			25°Stanchion Mount				Wall Bracket				Pendant Mount			Trunnion Mount			
	A	B	C	A	B	C	D	A	B	C	D	A	B	C	A	B	C	D
Inch	10.8	7.0	9.8	10.8	7.0	9.8	12.6	10.7	7.0	9.8	13.2	11.5	7.0	9.8	13.7	11.5	11.2	9.1
mm	274	179	248	275	179	248	320	271	179	248	336	292	179	248	348	292	284	230


MOUNTING OPTIONS



PHOTOMETRICS



ACCESSORIES



**Wire Guard**  
Wire guard 242\*242\*6mm  
Surface treatment: Nickel plating  
Color: Nickel color  
Code: BC-HA03-01