

Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

NOVA I MULTI WATTAGE & CCT SELECTABLE BULLET STYLE LANDSCAPE LIGHT





The Nova I Multi Wattage & CCT Selectable Bullet Style Landscape Light is designed for landscapers, designers, and homeowners. They are both wattage & CCT selectable to reduce inventory and increase flexibility at the job site. These fixtures can be surface mounted directly to electrical boxes or posts with a 1/2" threaded bushing. Optional yoke bracket and ground stake are available to meet different installation needs. They are available in 22°, 35°, 57°, and 110° beam spreads, allowing the lights to function as both spotlights and floodlights. The precision die-cast aluminum housing provides a sleek appearance and maximum durability. The luminaire is sealed to keep out dirt, bugs, and moisture, ensuring long-lasting performance.

FEATURES

- Field-selectable wattage & CCT
- Dimmable to fine tune light levels
- Photocell sensor automatically adjusts lighting based on ambient light
- Available in 22°, 35°, 57°, and 110° beam spreads
- IP65 rated

- ½" NPT threaded arm with locking swivel
- Wall mount or ground mount
- Suitable for uplighting and downlighting

APPLICATIONS

- Pathway
- · Garden and plant highlighting
- Flag pole
- Architectural accent
- Outdoor living spaces
- Security and safety
- Commercial and public spaces















NOVA I MULTI WATTAGE & CCT SELECTABLE BULLET STYLE LANDSCAPE LIGHT



ORDERING INFORMATION

MODEL#	WATTAGE SELECTABLE	INPUT VOLTAGE	CCT SELECTABLE	LUMEN RANGE	MINIMUM ORDER OTY	US STOCK
ECO-8BF-MW(6/12W)MCCT(30/40/50K)	6W 12W	100-277VAC or 200-480VAC	3000K 4000K 5000K	900-1,500	2	Yes
ECO-8BF-MW(12/20/28W)MCCT(30/40/50K)	12W 20W 28W	100-277VAC or 200-480VAC	3000K 4000K 5000K	2,100-3,780	2	Yes
ECO-8BF-MW(20/30/40W)MCCT(30/40/50K)	20W 30W 40W	100-277VAC or 200-480VAC	3000K 4000K 5000K	3,200-4,800	2	Yes
ECO-8BF-MW(25/35/45W)MCCT(30/40/50K)	25W 35W 45W	100-277VAC or 200-480VAC	3000K 4000K 5000K	4,125-6,250	2	Yes
ECO-8BF-MW(30/45/60W)MCCT(30/40/50K)	30W 45W 60W	100-277VAC or 200-480VAC	3000K 4000K 5000K	5,100-7,800	2	Yes

TECHNICAL SPECIFICATIONS

Input Voltage	100-277VAC
Input Power Frequency	50-60 Hz
Wattage Selectable	6W-12W 12W-20W-28W 20W-30W-40W 25W-35W-50W 30W-45W-60W
Power Factor	>0.90
THD	<20%
Efficacy	Up to 175 lm/W
Lumen Selectable	900-1,500 2,100-3,780 3,200-4,800 4,125-6,250 5,100-7,800
CCT Selectable	3000K 4000K 5000K
CRI	70+
Beam Angles	22° 35° 57° 110°
Controls	Wattage selectable, CCT selectable, dimmable, photocontrol
Operating Temperature	-22°F to 104°F
IP Rating	IP65
Certifications	cETLus wet listed, FCC
Construction	Die-casting Aluminum housing. Driver is thermally isolated to promote long-life. High-temperature silicone gaskets. Bronze finish standard. RAL & custom colors available.
Fixture Finish	Gray RAL7040
Mounting Options	Wall mount or ground mount
Warranty	10 years or 50,000 hour non-prorated


^{*}Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

^{*}IES files provided on request.



CONTROLS

Control Options: Wattage selectable, CCT selectable, dimmable, photocontrol.





OPTICS


Anti-glare & flicker-free optical lenses are available in 22°, 35°, 57°, and 110° spreads, allowing the lights to function as either spotlights or floodlights.



DIMENSIONS







NOVA I MULTI WATTAGE & CCT SELECTABLE BULLET STYLE LANDSCAPE LIGHT





MOUNTING OPTIONS

The fixture comes with ½" NPT threaded arm with locking swivel for easy wall or ground installation.

Creates an uplight or downlight effect. Can be mounted directly to electrical boxes or to poles with ½" threaded inserts.


Optional yoke bracket and ground stake are available to meet different installation needs.





ACCESSORIES

*All accessories sold separately.











Ecolite International, LLC, 7910 Wrenwood Blvd., Suite B, Baton Rouge, LA 70809