

|                     |               |
|---------------------|---------------|
| Project Name:       | Fixture Type: |
| Complete Catalog #: | Date:         |
| Comments:           |               |

## GEMINI HIGH POWER UP & DOWN COLUMN SCONCE-(RGB)



The **Gemini High Power Up & Down Column Sconce-(RGB)** is a high performance, color-changing, up/down wall sconce to add beautiful stripes of color to any building facade. The sconces highlight architectural details and minimizing glare. The durable die-cast aluminum housing has a silicone rubber seal, internal epoxy potting, and a variety of lens options. The fixtures are cETLus wet location listed and have a 10-year or 50,000 hour non-prorated warranty.

### FEATURES

- cETLus wet location listed
- up to 72W (2 x 36W)
- up to 100 lm/W
- 100-277VAC
- Beam angles: 15°, 25°, 45°, 60°, 90°, 120°
- Grey, black, white, and bronze finishes
- Die-cast aluminum and tempered glass housing
- Silicone rubber seal and internal epoxy potting
- DMX512 control

### APPLICATIONS

- Retail
- Residential
- Office
- Restaurant
- Hotel



## ORDERING INFORMATION

| MODEL NUMBER          | WATTAGE | VOLTAGE    | COLORS | MINIMUM ORDER QTY | US STOCK |
|-----------------------|---------|------------|--------|-------------------|----------|
| ECO-PR-GEM-10W-CS-RGB | 5W x 2  | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-12W-CS-RGB | 6W x 2  | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-18W-CS-RGB | 9W x 2  | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-24W-CS-RGB | 12W x 2 | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-36W-CS-RGB | 18W x 2 | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-48W-CS-RGB | 24W x 2 | 100-277VAC | RGB    | 2                 | Yes      |
| ECO-PR-GEM-72W-CS-RGB | 36W x 2 | 100-277VAC | RGB    | 2                 | Yes      |

## TECHNICAL SPECIFICATIONS

|                       |                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------|
| Beam Angles           | 15°, 25°, 45°, 60°, 90°, 120°                                                                   |
| LED Colors            | RGB                                                                                             |
| Total Wattage         | 10W, 12W, 18W, 24W, 36W, 48W, 72W                                                               |
| Input Voltage         | 100-277VAC                                                                                      |
| Power Frequency       | 50-60 Hz                                                                                        |
| Certifications        | cETLus wet listed, FCC                                                                          |
| Housing Material      | Die-cast aluminum with tempered glass lenses. Silicone rubber seals and internal epoxy potting. |
| Finish                | Grey, black, white, bronze                                                                      |
| Rated Life (L70)      | >50,000 Hours                                                                                   |
| Warranty              | 10 Years, 50,000 Hours Non-Prorated                                                             |
| Operating Temperature | -4°F to 104°F                                                                                   |
| Controls              | DMX512                                                                                          |

\*Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

\*IES files provided on request.

# GEMINI HIGH POWER UP & DOWN COLUMN SCONCE-(RGB)

## CONTROL OPTIONS

Control Option: DMX512

## DIMENSIONS

|                 |                   |                   |             |             |             |             |             |
|-----------------|-------------------|-------------------|-------------|-------------|-------------|-------------|-------------|
| Total Wattage   | 10W               | 12W               | 18W         | 24W         | 36W         | 48W         | 72W         |
| Dimensions (mm) | L65 x W100 x H230 | L65 x W100 x H230 | Φ110 x H300 | Φ110 x H300 | Φ145 x H300 | Φ160 x H300 | Φ180 x H300 |

## ACCESSORIES

Lens Options: 15°, 25°, 45°, 60°, 90°, 120°

