

Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

CHAMELEON II DOWN LIGHT



The Chameleon II Down Light has a deep reflector retrofit kit design. It comes in a complete size range of 4", 6", 8", and 9.5". Chameleon II is offered with two beam angles: 50° or 70° for the 4" and 6", and 40° or 60° for the 8" and 9.5" sizes. Its high lumen SMD light source enables adjustable CCT and adjustable power. The wet location design is suitable for a wide range of applications, including offices, supermarkets, shopping malls, schools, hotels, and more. It is ideal in stairwells, reception areas, and hallways. Premium performance features include: 103 lpW efficacy, 40 degree shielding angle, 3000K/4000K/5000K CCT selectable, 3-wattage selectable, two interchangeable beam angle reflectors, and an external driver with 1-10V dimming.

FEATURES

- 3-CCT selectable
- 3-Wattage selectable
- System Efficiency - up to 100 lm/W
- Up to 6200 lumens
- Input Voltage - 120-277VAC
- Wet location rated
- Rebate Eligible - Yes, contact for details
- Warranty - 10 Years or 50,000 Hours Non-Prorated

APPLICATIONS

- Offices
- Supermarkets
- Shopping malls
- Schools
- Hospitality
- Stairwells
- Reception areas
- Hallways



CHAMELEON II DOWN LIGHT

ORDERING INFORMATION

PART NUMBER	WATTAGE	LUMENS	VOLTAGE	DIMENSIONS	CCT	MIN ORDER QTY	US STOCK
ECO-UP-CHAM-30/40/50-4DL	10W/15W/20W	900/1300/1800	120-277VAC	6.0" X 6.0" X 5.0"	3000K/4000K/5000K	2	NO
ECO-UP-CHAM-30/40/50-6DL	20W/30W/40W	2200/3100/4000	120-277VAC	8.3" X 8.3" X 6.1"	3000K/4000K/5000K	2	NO
ECO-UP-CHAM-30/40/50-8DL	40W/50W/60W	4300/5200/6200	120-277VAC	10.3" X 10.3" X 7.1"	3000K/4000K/5000K	2	NO
ECO-UP-CHAM-30/40/50-9.5DL	40W/50W/60W	4300/5200/6200	120-277VAC	11.5" X 11.5" X 7.8"	3000K/4000K/5000K	2	NO

TECHNICAL SPECIFICATIONS

Beam Angle	50° & 70° for the 4" & 6", 40° & 60° for the 8" & 9.5"
CRI	80+
Efficacy	Up to 103 lpW
IP Rating	Wet location listed
Power Frequency	50-60 Hz
Power Efficiency	85% at full load
Power Factor	0.9
THD	< 20% @ 120VAC
Certifications	cULus, CE, FCC
Fixture Material	Magnesium alloy AZ91D
Rated Life (L70)	50,000 hours
Warranty	10 Years or 50,000 Hours Non-Prorated
Operating Temperature	-4°F to 104°F
Luminaire Gross Weight	3.0 lbs / 4.1 lbs / 5.3 lbs / 5.5 lbs

*Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

*IES files provided on request.

CONTROLS

Control Option: 1-10V dimming