

Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

SIGNATURE SELECT ALUMINUM LED EDGELIT EXIT SIGN



The **Signature Select Aluminum LED Edgelit Exit Sign** is ideal for applications requiring attractive, thin-profile, die-cast aluminum signage, superior illumination and low energy consumption. These exit signs provide a thin-profile, lightweight alternative to traditional exit signs. The sleek, modern, edgelit design enhances contemporary building designs. A self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation, and the signs meets BAA, UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

FEATURES

- Dual circuit option on the AC-only unit enables it to be connected to two different power supplies.
- Buy American Act (BAA) compliant
- Self diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation.
- UL listed for damp applications
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

APPLICATIONS

- Stairways
- Hallways
- Paths of egress



SIGNATURE SELECT ALUMINUM LED EDGELIT EXIT SIGN

ORDERING INFORMATION

PART NUMBER	LETTER COLOR	NUMBER OF FACES	PANEL	HOUSING COLOR	BATTERY	SPECIAL OPTIONS	MIN ORDER QTY	US STOCK
ECO-HSL-ELXTEU1RCAEM	RED	Single/ Double	Clear ¹ Mirror White	White Black Aluminum	AC Only/ Battery Backup	Self-diagnostics ² / Custom Wording/Dual Circuit Operation ³ / 208, 220, 240V ⁴	2	YES
ECO-HSL-ELXTEU1GCAEM	GREEN	Single/ Double	Clear ¹ Mirror White	White Black Aluminum	AC Only/ Battery Backup	Self-diagnostics ² / Custom Wording/Dual Circuit Operation ³ / 208, 220, 240V ⁴	2	YES

Notes:

¹ With single face only

² Available only with EM units

³ Available only with AC units

⁴ Not available with SDT

TECHNICAL SPECIFICATIONS

Input Voltage	Dual 120/277 voltage standard. Optional multi-tap 208/220/240 voltage available
Wattage	3.6-4.0W, depending on options selected
Input Current	0.03A at 120V, 0.02A at 277V
Certifications	BAA, UL924, NFPA 101 Life Safety Code, NEC, OSHA, local & state codes
Environment	Damp location listed
Fixture Material	Aluminum and polycarbonate
Operating Temperature	32° - 122° F
Testing	Self diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation
Mounting	Aluminum mounting canopy included for top, end or back mount
Battery	4.8V, long life, maintenance-free, rechargeable NiCd battery
Emergency Operation	>90 minutes of emergency illumination

*Data is based upon tests performed in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

*IES files provided on request.

SIGNATURE SELECT ALUMINUM LED EDGELIT EXIT SIGN

DIMENSIONS

